



## Automatic label applicator LPA.430

### Quick and Precise Labeling on Moving Products.

**LPA.430 applicator** is the answer. Designed for businesses that can't afford interruptions, this high-frequency linear labeling system is designed to seamlessly integrate your production line, ensuring the highest application quality on every product on the go. It's not just about applying labels: it's about optimizing your processes and ensuring flawless traceability.

**COD:** PSG-LPA.430S.AF

**PLURISERVICE CODE** PSG-LPA.430S.AF



Produzione

## DESCRIPTION

- **Speed and Accuracy:** With an application speed of up to 30 m/min, the LPA.430S handles large volumes while maintaining absolute precision. Its ability to label products sequentially and on the go makes it ideal for dynamic manufacturing environments.
- **Maximum Adaptability:** This applicator works with a wide range of materials, including labels on coated, glossy, metallic and thermal paper, offering unparalleled versatility. Supports label widths from 25.4mm to 118mm, adapting to your specific needs.
- **Intuitive Control:** The backlit TOUCH color display makes for immediate use. You can easily adjust distribution speed, label feed and counters with a simple tap. The password-protected menu allows you to save up to 40 programs, ensuring rapid production changes and operational security

## TECHNICAL SPECIFICATIONS

- **Supporti utilizzabili:** Etichette in rotolo, carta patinata, lucida, carta metallizzata, carta termica.
- **Dimensioni rotolo etichette:** Ø interno 42 / 76 mm - Ø esterno 345 mm
- **Larghezza min - max. etichette:** da 25,4 mm a 118 mm
- **Velocità di applicazione:** Fino a 30 m/min.
- **Massima trazione rotolo etichette:** Kg.10
- **Peso:** kg 38 circa.
- **Alimentazione di rete:** 220 Volt - 50Hz.
- **Dimensioni ingombro:** Larghezza 900 mm Altezza. 540 mm Prof. 350 mm